



**New High Performance
Award Winning Design
240VAC To 12V @ 5A / 15A / 30A
LEAD ACID BATTERY CHARGER**

Features:

- Innovative 4 stage fully automatic charger for optimal fast charging and extended battery life
- Award winning microprocessor design insures accurate charging parameters with unique zero power consumption when not connected to the battery
- Low ripple charge and fully operational from 180VAC To 250VAC
- Compact heavy duty aluminium construction
- Fully protected against overload, over temperature and battery connection reversal
- No sparks connection
- Innovative voltage free leads with no power dissipation when disconnected
- Selectable output current between 5 Amp, 15 Amp and 30 Amp
- Available in custom charge rates, Conditions Apply.



Specifications	BC240-1230-S
Normal voltage	Auto Select 12V
Bulk Charge Current	5A/ 15A / 30A
Dimensions[LxHxW]	210 X 65 X 160 mm
Float at 12V mode	13.5V
Bulk at 12V mode	14.5V
Safety	AS/NZS 3350.2.29
Protection	Over Temperature, Over Current, Over Voltage, Reverse Polarity, Bulk charge timeout, Voltage free leads without battery
Weight	1.8 Kg
Standby consumption	Below 1W



CONTACT W: www.gsl.com.au
GSL: PH: (02) 9620 9988