



## New High Performance Award Winning 4 Stage Dual Chemistry 240VAC to 48VDC @ 10AMP BATTERY CHARGER

### Features:

- Innovative 4 stage fully automatic charger for optimal fast charging and extended battery life
- Award winning microprocessor design insures accurate voltage and current charging parameters
- Low ripple charge and fully operational from 180VAC To 250VAC
- Compact heavy duty aluminium construction
- Fully protected against overload, over temperature and battery reversal
- No spark connection
- Innovative voltage free leads with no power dissipation when disconnected
- Dual battery chemistry, selectable lead acid or calcium batteries
- Custom charge voltages between 32V and 62V available upon request\*



BC240-4810

Specifications	BC240-4810
Normal voltage	48V
Bulk Charge Current	10A
Dimensions[ LxHxW]	210 X 65 X 160 mm
Float lead acid voltage	54V
Bulk lead acid voltage	58V
Float Calcium voltage	56V
Bulk Calcium voltage	62V
Safety	Designed to comply with AS/NZS 60950
Protection	Over Temperature, Over Current, Over Voltage, Reverse Polarity, Bulk charge timeout, Voltage free leads without battery
Weight	2.2 Kg
Standby consumption	Below 1W



**CONTACT W:** www.gsl.com.au  
**GSL: PH:** (02) 9620 9988