



24V TO 12VDC Switchmode BATTERY CHARGER

Features:

- High efficiency switchmode technology
- Control wire via ignition
- Automatic 2 stage charge
- Current and Voltage limiting protection
- Compact and lightweight aluminium heatsink construction
- Output over voltage protection
- Applicable where there are high current drain loads e.g. winches, rear lift platforms



Specifications	BC2412-10	BC2412-20	BC2412-30
Input Voltage	20V to 28VDC	20V to 28VDC	20V to 28VDC
Output Voltage	14V \pm 3%	14V \pm 3%	14V \pm 3%
Efficiency % @ Full Load	\geq 90%	\geq 90%	\geq 90%
Output Current	10Amps	20Amps	30Amps
Stand By Current (Approx)	50mA	70mA	70mA
Short Circuit Protection	Yes	Yes	Yes
Input To Output Protection	Yes	Yes	Yes
Thermal Protection	No	Yes	Yes
Output Connections - 4 Fly Leads	Yes	Yes	Yes
Dimensions mm (L x W x H)	90 x 135 x 60	155 x 135 x 60	175 x 135 x 60
Weight	0.6Kg	1.2Kg	1.3Kg

CONTACT W: www.gsl.com.au
GSL: PH: (02) 9620 9988