



## New High Performance 12V Multi Chemistry BOOSTER CHARGER

### Features:

- Australian award winning microprocessor design ensures accurate voltage and current charging parameters from as low as 9.2V input
- Automatic 3 stage charging ensures optimal fast charge and extended battery life
- Low minimum input voltage compensates for voltage drop in long cable lengths between main and auxiliary battery
- Selectable chemistry switch enables accurate charge voltage for AGM/GEL/FLOODED batteries
- Fan cooled light weight aluminium heat sink construction
- Short circuit protection
- Over temperature protection
- Over current protected
- Reverse polarity protected
- No spark connection to auxiliary battery



MCB-1225

“Best dual/auxiliary battery charging system on the market...”

Specifications	MCB-1225
Lowest Operating Voltage	9.2V
Maximum Operating Voltage	15V
Maximum Current at Bulk Charge	25A
Charge Voltage for Flooded Cell	14.6V
Charge Voltage for AGM	14.4V
Charge Voltage for GEL	14.2V
Float Voltage	13.5V
Dimensions cm (LxWxH)	17.5 x 13.5 x 6.3
Weight	1.4 Kg

**CONTACT** W: [www.gsl.com.au](http://www.gsl.com.au)  
**GSL:** PH: (02) 9620 9988