



**New High Performance
24V To 12VDC
Available in 40A and 60A
SWITCHMODE BATTERY CHARGER**

Features:

- Microprocessor based, 3 stage fast charge
- High efficiency switchmode technology
- High reliability and longer battery life
- Control wire with delayed reaction to avoid cold cranking problems
- Battery detection avoids connection reversal and sparking problems
- Time out on bulk charge to avoid battery charge
- Current limiting under overload and short circuit conditions
- Compact and light weight aluminium heatsink construction



Specifications	REC-1240C	REC-1260C
Input Voltage	23 to 30VDC	23 to 30VDC
Output Voltage Absorption/Float	13.5V ± 1%	13.5V ± 1%
Output Voltage Bulk charge	14.5V ± 1%	14.5V ± 1%
Efficiency at typical operating conditions	≥ 85%	≥ 85%
Bulk charge current	40 Amps	60 Amps
Stand by Current	20mA	20mA
Short Circuit and Battery reversal Protection	Yes	Yes
Over Voltage Protection	Yes	Yes
Thermal Protection	Yes	Yes
Input and charge status indication	Yes	Yes
Output Connections	Fly Leads	Fly Leads
Dimensions L x W x H mm	285x175x65	285x175x65
Weight	2.5Kg	2.6Kg

CONTACT W: www.gsl.com.au
GSL: PH: (02) 9620 9988