



12V To 24VDC Voltage Doublers Single / Multi Circuit

Features:

- High efficiency switchmode technology
- Longer life operation
- Soft start - via control wire
- Overload protection
- Input to output protection
- Compact and lightweight aluminium heatsink construction
- Suitable for most automotive, marine and industrial applications



Specifications	VI1224-5	VI1224-10	VI1224-15*	VI1224-20*
Input Voltage DC	11V to 15V	11V to 15V	11V to 15V	11V to 15V
Output Voltage DC	26.5V	26.5V	27V	27V
Number Of Circuits	Single	Single	Single	Single
Stand-by Current	26mA	28mA	140mA	140mA
Full Load Current	5A	10A	15A	20A
Load Regulation (1)	± 5%	± 5%	± 5%	± 5%
Input To Output Protection	Yes	Yes	Yes	Yes
Connection - Fly Leads	Yes	Yes	Yes	Yes
Dimensions mm (L x W x H)	90 x 135 x 60	90 x 135 x 60	155 x 135 x 60	155 x 135 x 60
Weight	0.7Kg	0.7Kg	1.3Kg	1.3Kg

* Denotes Encapsulated

Note (1): With vehicle engine running.

CONTACT W: www.gsl.com.au
GSL: PH: (02) 9620 9988